

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6364-65)

-----  
Set ¼ sec. post, from which  
A B.Oak 14" dia., bears S.45°E., 14 lks. dist.  
A Pine 18" dia., bears S.30°W., 10 lks. dist.

J.H. Markham, Jr. - Wit: Frank White - For: Paul Barber - C.S. File 41/102-2

-----  
Determined by proportional measurement.  
At midpoint on section line, I set a ½" x 12" I.P., from which  
A Yellow Pine 22" bears N.66°W., 6.0 ft. mkd. ¼S S14 BT.  
A Cedar 10" bears N.44°E., 18.0 ft. mkd. ¼ S S13 BT.  
NE. Cor. 14 bears North 2570 ft.  
SE. Cor. 14 bears South 2570 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - April, 1963 - C.S. File 52/126-100

-----  
Found - Both BTs scribed by Markham.  
22" now 24" Pine stump, N.66°W., 6.0 ft., shows good scribing.  
NE. BT down, shows scribing.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 29 S R 4 W  
S14|S13  
1963  
New BTs -10" Cedar bears S.76°E., 42.6 ft. scribed ¼ S13 CSBT  
15" Cedar bears S.25°W., 27.3 ft. scribed ¼ S14 CSBT

Fd. & used on BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1775, surveyed Aug./Sept.. 1995 - (DCSO records Vol. 52 Page(s) 19942-3)

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 7/31/2000 - C.S. File 66/16-29

-----  
Found - 1963 DCSO 36" long BC/IP out of ground.  
22" Y.Pine now rotted stump, no scribing visible bears N.66°W., 6.0 ft. 1952  
10" now 14" dia., down I.Cedar w/fully healed single blaze, root hole bears S.76°E., 42.6 ft. 1963  
15' now 18" dia., I.Cedar with a fully healed single blaze bears S.25°W., 27.3 ft. 1963  
continued next page

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Reset -	1963 DCSO BC/IP, protrudes 2" above ground, add stamping "RESET 2000"
New -	33" dia., D.Fir single blazed & scribed "¼ S13 CS BT" bears N.77°E., 25.0 ft.
	12" dia., I.Cedar double blazed & scribed "¼ S14 CS BT" bears S.85°W., 52.0 ft.
	18" dia., D.Fir double blazed & scribed "¼ S13 CS BT" bears N.10½°E., 60.5 ft.