

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 600460

PRIMARY CORNER DESCRIPTION North 1/16 cor. for secs. 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

J.H. Markham, Jr. - Wit: Frank White - For: Paul Barber -  
C.S. File 41/102-1 (12/31/1952)

-----  
On midpoint on the section line between E ¼ cor. and the NE.  
corner of section 14.

I set a 2" x 2" wood post, from which

A Fir 32" dia., bears N.60°E., 10.0 ft. mkd. with a bark  
scribed 1/16 S BT.

A Fir 10" bears S.21°W., 12.5 ft. mkd. 1/16 S BT.

¼ corner bears South 1285 ft.

NE. corner bears North 1285 ft.

-----  
Don Martin - For: Charles & Norma Lawrence -12/1968 - M39-21

Set - 3/4" IP

BTs - 12" Cedar N.46½°W., 26.0'

24" D.Fir N.26½°E., 42.3'

-----  
BLM dependent resurvey by Bryan S. Seibold, Cadastral  
Surveyor & Robert H. Browning, Surveying Technician, under  
Group #1775, surveyed Aug./Sept.. 1995 - (DCSO records Vol.  
52 Page(s) 19943-4)

-----  
The N 1/16 sec. cor. of secs. 13 & 14, established by Martin,  
in 1968, recorded on M39-21, and is accepted as the corner;  
monumented with an iron pipe, 1" diam., firmly set,  
projecting 18" above ground, from which the remains of  
bearing trees mkd. by Martin:

A fir stump, 17" diam., bears N.29¼°E., 57 lks., no marks  
visible.

A cedar, 16" diam., bears S.50½°W., 38 lks., with scribe  
marks 1/16 S14 BT visible on partially healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 25" in the  
ground, directly over the iron pipe, with brass cap mkd.

N 1/16  
S 14 | S 13  
1995

from which a new bearing tree

A cedar, 11" diam., bears N.18 3/4°E., 19 lks., mkd. N1/16  
S13 BT.

From this point, the Bureau of Land Management Geodetic  
Control Station No. EC41119, at latitude 43°03'04.391" N.,  
longitude 123°07'52.304"W. (NAD 1927), determined by the  
NAVSTAR Global Positioning System in 1991, bears N.28°26'54"  
E., 5.776 chs. dist. (mean bearing and sea level dist.);  
monumented with an aluminum cap, 3¼" diam., firmly set flush  
with the ground, with top mkd. EC41119 GPS 1991.

---