

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Pg 6389)

Marked a Laurel 24" dia., for the cor. to Secs. 1, 2, 11 and 12, from which

- A Laurel 10" dia., bears N.30°E., 58 lks. dist.
- A Cedar 10" dia., bears S.45°E., 30 lks. dist.
- A Cedar 12" dia., bears S.20°W., 24 lks. dist.
- A Laurel 12" dia., bears N.30°W., 44 lks. dist.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones and W. Penley, crew - July 23, 1969 - C.S. File 49/67-43

Found - 24" Laurel corner tree, rotted center.
Orig. 10" now 20" Cedar, burnt face, S.45°E., 19.8 ft. partly visible scribe.
Orig. 12" now 29" Cedar, burnt face, S.20°W., 15.8 ft. scribe visible. Reblazed and rescribed T29S R4W S11 CS BT.
Orig. 10" now 18" Laurel N.30°E., 38.3 ft., rotten face, parts of scribing visible.
Orig. 10" Laurel, now down, N.30°W., 29.0 ft. scribe visible and other marks, face rotten.

Set Brass cap at cor. mkd: County Surveyors Office

T 29 S R 4 W
S 2 | S 1
S 11 | S 12
1969

New BTs -27" Laurel N.15°E., 23.2 ft. mkd. T29S R4W S1 CS BT
9" Laurel N.45°W., 2.0 ft. mkd. T29S R4W S2 CS BT.
29" Cedar S.20°W., 15.8 scribed T29S R4W S11 CS BT

Fd. ok by D.Edwards, March 1998 - M 128-43

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, under Group No. 2300: Admin. file #0602, surveyed May/June 2006 - (DCSO recs Vol. 56 Pg 22315 & Plat T29-4 2011-3)

The cor. of secs. 1, 2, 11, & 12, perpetuated by Powell in 1969, monumented with an iron post, 1¼" dia., firmly set, projecting 15" above ground, (projecting from the decayed middle of a madrone snag, 27" dia., with axe marks visible on NE, SE & NW faces), with brass cap (properly) mkd.

from which the remains of the orig. BTs
A cedar, 22" dia., bears S.38½°E., 21.4 ft. with a healed blaze. (Rec. S.45°E., 19.8 ft.)
A cedar, 30" dia., bears S.20°W., 18.3 ft. with a healed blaze (Rec. 15.8 ft) continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A root hole bears N.30°W., 29.0 ft. with no trunk remains. and remains of BTs mkd by Powell
A madrone, 25" dia., bears N.14½°E., 23.6 ft. with fragmentary scribe marks visible on a partially healed blaze.
A madrone stump, 10" dia., bears N.55¼°W., 2.0 ft with a healed blaze.
and new BT
A fir, 12" dia., bears N.55¼°W., 21.5 ft., mkd: T29S R4W S2 BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

Ken Hoffine - For: Lone Rock Timber Co. - Feb. 2011 - M157-39

Found - 1969 county cap in center of rotten madrone remains.
10" madrone stump bears N.41°W. 1.8 ft (rec N.45°W., 2.0 ft) BT and tag
21" cedar bears S.39¼°E., 21.2 ft (rec S.45°E., 19.8 ft) healed face and tag
27" cedar bears S.19½°W., 16.3 ft (rec S.20°W., 15.8 ft) burnt face
12" D.Fir bears N.55½°W., 24.8 ft, no record BT tag that reads S.55¼°E., 21.5 feet corner lies on south facing slope approximately 150 feet west of clear-cut.

BLM resurvey by George M. Winter, Cadastral Surveyor, under Group No. 2747, surveyed May/July 2014 - (DCSO records Vol. 58 page(s) 23196-7)

The cor. of secs. 1, 2, 11, & 12, monumented with an iron post, 1¼" dia, firmly set, projecting 15" above ground, encircled by the decayed remains of the original madrone corner tree, with brass cap (properly) mkd.
from which the remains of the original bearing trees
A cedar, 23" dia, bears S.38½°E., 21.4 ft., with a healed blaze.
A cedar, 28" dia, bears S.20°W., 16.3 ft., with a healed blaze. (Record, 18.3 ft.)
and remains of a BT mkd. by the Douglas County Surveyor's Office in 1969
A madrone snag, 23" dia, bears N.14½°E., 23.6 ft., with fragmentary scribe marks visible.
and remains of a bearing tree mkd. by Skeesick in 2006
A sawed fir stump, 13" dia, bears N.55¼°W., 21.5 ft., with a healed blaze.
continued next page

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and new bearing trees
A fir, 13" dia, bears N.10¼°E., 13.8 ft., mkd. T29S R4W S1
BT
A cedar, 5" dia, bears N.38°W., 5.4 ft., mkd. X BT.
NAD 1983 (2011)
Latitude: 43°04'04.03"N Longitude: 123°07'59.05"W