

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6362)

Set 1/4 sec. post at average dist., from which
A B.Oak 10" dia., bears N.33°E., 85 lks. dist.
A B.Oak 12" dia., bears S.27°W., 65 lks. dist.

Douglas Co. Surveyors Office - Arthur R. Evans, Deputy - Crew, F.D. Smith; Harvey Potter; Ivan Taylor - May 1949 - C.S. File 43/94; Vol. 5 Pg. 17; and M 1-31

Set 3/4" x 36" G.I.P. for corner.
Blazed and scribed BTs:
15" Cedar S.58°E., 23.8 ft. mkd. T29S R4W 1/4 S36 CS BT.
10" Fir N.77°W., 21.8 ft. mkd. T29S R4W 1/4 S25 CS BT.
Nailed brass disk to Fir BT, mkd. Co. Surv. Off., 1/4 Cor. 25/36 set by Rg. Engr. Ore. No. 2741.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - April 1963 - C.S. File 52/126-124

Found - 3/4" I.P. at corner.
15" Cedar S.58°E., 23.8 ft., snag.
10" Fir N.77°W., 21.8 ft., now stump.
New BTs - 8" W.Fir S.72°E., 20.5 ft. scribed 1/4 S36 CS BT.
9" Laurel N.10°E., 48.3 ft. scribed 1/4 S25 CS BT.

Found OK by R. Rice, June 2003 - M142-46

David Edwards - For: Seneca Jones Timber Co. - 11/2009 - M160-11

Found - 3/4" dia., IP, per M1-31
Both BTs from M1-31 are gone.
BTs w/tags dated 2003, (1963 BTs):
13" dia., madrone bears N.20°E., 48.3'
10" dia., fir bears S.72°E., 20.5'