

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6363)

Set ¼ sec. post at average dist., from which
A Red Fir 30" dia., bears N.28°E., 33 lks. dist.
A Red Fir 10" dia., bears S.46°W., 27 lks. dist.

M.B. Germond - Sept. 1908 - Field Book 19 Pages 41-42

I set for ¼ corner, a Yew wood post 4" x 4" x 3 ft. from which
White Fir 6" dia., S.45°12'E., 22 lks.
Maple 6" dia., N.31°48'W., 6 lks.

Arthur Evans, Deputy Co. Surveyor - Wit: F.D. Smith; Harvey Potter; Ivan Taylor - May 1949 - M 1-31

Set by proportionate measurement, Set 1¼" x 30" I.P. 6" underground.
Blazed and scribed BTs:
30" Cedar N.10½°W., 28.6 ft. mkd. T29S R4W S24 CS BT.
6" Fir S.16¼°E., 28.4 ft. mkd. T29S R4W ¼ S25 CS BT.
Nailed brass disk to 30" Cedar mkd. Co. Surve., ¼ cor.
24/25 set by Reg. Engr. Ore. No. 2741.

Fd. OK, Jan. 1995 by R. Brown - M 121-38

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #'s 255; 701; 938 - Surveyed July 1967/Oct 1977 (DCSO records Vol. 39 Page(s) 15862)

The ¼ sec. cor., reestablished at proportionate distance by Evans in 1949, monumented with an iron pipe 1¼" dia., firmly set, projecting 8" above ground. There is no remaining evidence of the original corner; therefore, this position is accepted as the corner, from which bearing trees mkd. by Evans:

A Cedar 30" dia., bears N.12 3/4°W., 43 lks. dist. with scribe marks ¼ S24 CS BT visible on partially healed blaze and a brass disc nailed to tree mkd. DOUGLAS COUNTY SURVEYOR ¼ CORNER 24 25 set by REG. ENGR. 2741 ORE.

A Fir 9" dia., bears S.18½°E., 41½ lks. dist., with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, directly over iron pipe, with brass cap mkd:

(Cont. Next Page)

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

T 29 S R 4 W ¼ $\frac{S\ 24}{S\ 25}$ 1967
Fd. OK, Jan. 1995 by R. Brown - M 121-38
James Klein - For: Williams/Pacific Connector Gas Pipeline Project - 7/2015 - M166-44 A-F ----- Found - 3¼" brass cap stamped BLM 1967 19" fir with healed face, set new tag dated 6/14, S.18½°E., 27.4' 36" cedar with healed face brass disk is attached to tree & tag dated 10/67, N.12¾°W., 28.4'