

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 24

Alias	Description

Floyd Frear; M.B. Germond, Co. Surveyor - Aug. 1918 - Vol. 3
Pg. 25 and M 1-33 (Cody & Black survey)

Set 1" x 36" I.Pipe for center of section.
New BTs -24" Fir S.88½°W., 7½ lks.
8" Fir N.35 3/4°W., 20 lks.
24" Fir N.38½°E., 51 lks.
18" Cedar N.80½°E., 28½ lks.

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral
Surveyors under Group #'s 255; 701; 938 - Surveyed July/Oct
1977 (DCSO records Vol. 39 Page(s) 15911)

Point for the center ¼ sec. cor. of sec. 24, at intersection
with the E. and W. center line.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with
brass cap mkd: T 29 S R 4 W
 C ¼ S 24
 1977

from which
A Fir 6" dia., bears N.50½°E., 67½ lks. dist., mkd. C ¼
S24 BT.
A Fir 6" dia., bears S.60½°W., 12½ lks. dist., mkd. C ¼
S24 BT.

From this point, a corner established by F.C. Frear in 1918,
bears N.66°30'E., 0.23 chs. dist., monumented with an iron
pipe, 3/4" dia., firmly set, projecting 1" above ground, from
which the remains of a bearing tree mkd. by Frear:

A decayed Fir stump 10" dia., bears N.33°W., 20 lks.
dist., with fragmentary scribe marks visible on decayed
blaze.

Fd. OK, Jan. 1995 by R. Brown - M 121-38