

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6365)

Set ¼ sec. post at average dist., from which
A Yew 4" dia., bears N.75°W., 75 lks. dist.
A Red Fir 18" dia., bears S.65°W., 15 lks. dist.

GL0 survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6388)

¼ sec. cor. Witness trees standing, viz:
A Yew 4" dia., bears N.75°W., 75 lks. dist.
A Red Fir 18" dia., bears S.65°W., 15 lks. dist.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #255 - Surveyed Sept. 2-9, 1964 - (DCSO records Vol. 33 Page(s) 13875-76)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:
T 29 S R 4 W
¼ S 12
S 13
1964
from which
A Fir 38" dia., bears North 66 lks. dist. mkd. ¼ S12 BT.
A Fir 17" dia., bears S.8½°W., 20 lks. dist. mkd. ¼ S13 BT

Fd. ok by D.Edwards, March 1998 - M 128-43

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor & Robert H. Browning, Surveying Technician, under Group #1775, surveyed Aug./Sept.. 1995 - (DCSO records Vol. 52 Page(s) 19946)

The ¼ sec. cor. of secs. 12 & 13, monumented with an iron post, 2½" diam., firmly set, projecting 5" above ground, with brass cap mkd.
T29S R4W
¼ S 12
S 13
1964
from which the remains of bearing trees mkd. by Beck
A root hole, bears North, 66 lks. dist., with down fir alongside, 33" diam., with healed blaze.
A fir, 24" diam., bears S.8½°W., 20 lks., with healed blaze.
continued next page

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and a new bearing tree
A cedar, 9" diam., bears N.22°W., 22 lks., mkd. ¼ S12 BT.

Mark Smalley - For: Roseburg Resources - 9/2003 - C.S. File
65/48-19

Found - 1964 BLM IPBC (properly mkd)
24" Fir S.8½°W., 13.2 healed.
9" Cedar, N.22°W., 14.5 scribe visible.
Fir North 43.6 down - rotten
New - 7" Cedar S.62°W., 9.0 scribed "¼ S13 BT"
7" Fir N.20°E., 16.1 scribed "¼ S12 BT"