

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6299)

Set ¼ sec. post, from which
A Red Fir 24" dia., bears S.55°W., 35 lks. dist.
A B.Oak 4" dia., bears S.65°E., 75 lks. dist.

GLO survey by Dennis Hathorn, under Contract #73, dated June 8, 1857 (DCSO records, Vol. 15 Page 6309)

¼ sec. post E. bdy. Sec. 36.

Cor. Fd. and tied in GLO Survey by W.H. Byars, Contract #376 dated Jan. 22, 1881 (DCSO Records Vol 15 Page 6317)

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13787)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 29 S
¼
S 36
R 4 W
1964

from which

A Cedar 10" dia., bears S.57¼°W., 16 lks. dist. mkd. ¼ S36 BT.

A Cedar 7" dia., bears N.22¼°W., 39 lks. dist. mkd. X at breast height and BT at the base.

Found OK by R. Rice, June 2003 - M142-46

Fd. BC & 2 BTs by D.Edwards, 1/2009 - C.S. file 65/67-1 SET 6 ft. steel post 2' north

Michael Erickson & Leonides Sadoval - For: Ensite USA - 4/2019 - M171-67A

Found - 1964 3" BLM Brass cap
15" cedar with healed blaze, N.22°W., 26.0' to face.
14" cedar with healed blaze, S.57°W., 11.0' to face.
15" madrone with visible blaze S.0°E., 9.0' to face.

- **No record**