

PRIMARY CORNER DESCRIPTION Sec Cor for 25 & 36 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6299)

Set a post, cor. of secs. 25, 30, 31 and 36, from which
A B.Oak 8" dia., bears S.30°E., 50 lks. dist.
A B.Oak 8" dia., bears N.37°E., 80 lks. dist.
A W.Oak 10" dia., bears N.32°W., 100 lks. dist.
A B.Oak 16" dia., bears S.15°W., 95 lks. dist.

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6317)

Old sec. cor., set post as per instructions. Witness trees all standing, viz:
Oak tree 8" dia., bears S.30°E., 50 lks.
Oak tree 8" dia., bears N.37°E., 80 lks.
Oak tree 10" dia., bears N.32°W., 100 lks.
Oak tree 16" dia., bears S.15°W., 95 lks.

Arthur R. Evans, Deputy Co. Surveyor, LS #2741 - Wit: F.D. Smith; Harvey Potter; Evan Taylor - May 1949 - M 1-31

Set 1" Galv. I.P. with brass cap mkd. "Co. Surv. Off. T29S R4W Sec. Cor. 25 36 R.E. 2741".
Blazed and scribed BTs:
15" Fir N.80°W., 21.3 ft. mkd. T29S R4W S25 CS BT.
18" Fir S.26°W., 27.7 ft. mkd. T29S R4W S36 CS BT.
Found old BTs:
W.Oak stump N.32°W., definite axe marks and 2 distinct blazes, dead and face of blaze rotted.
B.Oak, N.37°E., down and rotted, but axe marks and blaze definite.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. S. Stoffel crew - Nov. 1962 - C.S. File 52/126-76

Found - Stump of SW. BT as recorded by Evans, shows good bark scribing "BT". No trace of NW. BT.
No trace of brass cap set by Evans.
This area has been disturbed by logging roads.
Set Brass cap at cor. mkd: County Surveyors Office
S 25 | T29S
R4W S 36 | R3W
1962
New BTs -14" Cedar bears S.21°W., 123.0 ft. scribed S36 T29S R4W CS BT.

(Cont. Next Page)

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec Cor for 25 & 36 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>18" Cedar bears N.84°W., 88.2 ft. scribed S25 T29S R4W CS BT.</p>
<p>BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13787-88)</p> <p>-----</p> <p>The Sec. cor., perpetuated and recorded by Evans in 1949, from the remains of the original bearing trees which are no longer in existence. In 1962, Byron remonumented the corner from the remains of the Evans' BT, with an iron post, 1" dia., 12" above ground, firmly set with properly mkd. brass cap, from which the Evans bearing tree: A sawed Fir stump 18" dia., bears S.26°W., 42 lks. dist. mkd. BT on detached bark. and bearing trees mkd. by Byron: A Cedar 18" dia., bears S.21¼°W., 200 lks. dist. mkd. T29S R4W S36 CS BT on double blaze. A Cedar 20" dia., bears N.85°W., 133 lks. dist. mkd. T29S R4W S25 CS BT on double blaze. Add the marks BLM to the brass cap.</p>
<p>Fd. BC & 2 BTs by D.Edwards, 1/2009 - C.S. file 65/67-1 SET 6 ft. steel post 2' south</p>
<p>James Klein - For: Williams/Pacific Connector Gas Pipeline Project - 7/2015 - M166-44 A-F</p> <p>-----</p> <p>Found - 2½" brass cap stamped County Surveyors Office 1962 New - 13" cedar (scribed X BT) N.8°E., 20.7' to nail side center. 7" cedar (scribed X BT) S.18°W., 16.4' to nail side center. 10" cedar (scribed T29S R4W S25 BT) N.35°W., 12.4' to nail side center.</p>