TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 700229

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 30 only, T29-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

---

GLO survey by Dennis Hathorn, Contract #73 dated June 8, 1857 (DCSO records, Vol. 15 Page 6311)

---

Set ¼ sec. post, W. bdy. Sec. 30, from which
An Oak 12" dia., bears N.58°E., 99 lks. dist.
An Oak 10" dia., bears S.80°E., 49 lks. dist.

---

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13788)

---

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 25" in the ground, with brass cap mkd:

```
| T 29 S
| ¼
| S 30
| R 3 W
1964
```

from which
A Fir 10" dia., bears N.41½°E., 29½ lks. mkd. ¼ S30 BT.
A Cedar 13" dia., bears S.85½°E., 13 lks. mkd. ¼ S30 BT.

---

James Klein - For: Williams/Pacific Connector Gas Pipeline Project - 7/2015 - M166-44 A-F

---

Found - 3¼" brass cap stamped BLM 1964
Fir snag with healed face, no tag, N.41½°E., 19.5'
New - 8" cedar (scribed ¼ S30 BT) N.75°E., 23.2' to nail side center.
24" fir (scribed X BT) N.72°W., 9.55' to nail side center.

---