

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 700272

PRIMARY CORNER DESCRIPTION Sec. cor. for 19 & 30 only, T29-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Contract #73, dated June 8, 1857 - (DCSO Records, Vol. 15 Page 6311)

Set post cor. secs. 19 and 30, from which
A Fir 40" dia., bears N.30°E., 70 lks. dist.
A Laurel 12" dia., bears S.80°E., 33 lks.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13790)

Point for the cor. of secs. 19 and 30 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 28" long 2½" dia., 22" in the ground, with brass cap mkd: T 29 S T 29 W

 S 25 S 19
 S 30
 R 4 W R 3 W
 1964

from which
A Fir 20" dia., bears N.53°E., 37 lks. dist. mkd. T29S R3W S19 BT.

A Cedar 12" dia., bears S.13 3/4°E., 46 lks. dist. mkd. T29S R3W S30 BT.

The corner is located at the SW. corner of a logged area, edge bears N. and E.