

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24 only (East)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6298)

-
- Set a post cor. of secs. 13, 18, 19 and 24, from which
- A Laurel 14" dia., bears S.65°E., 50 lks. dist.
 - A Laurel 6" dia., bears N.20°E., 10 lks. dist.
 - A Laurel 10" dia., bears N.35°W., 65 lks. dist.
 - A Laurel 16" dia., bears S.50°W., 58 lks. dist.

GLO survey by W. H. Byars, found all trees standing, under contract #376, dated Jan. 22, 1881 - (DCSO records, Vol. 15 Page 6316)

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13792-93)

-
- The cor. of secs. 13 and 24 only, determined at record distance from the remains of the original bearing trees:
- A Madrone stump hole bears N.20°E., 10 lks. dist.
 - A Madrone stump hole bears S.65°E., 50 lks. dist.
 - A Madrone stump hole bears S.50°W., 58 lks. dist.
 - A Madrone stump hole bears N.35°W., 64 lks. dist. (Record bearing by Byars, N.5°W.)
- All the stump holes have young madrone trees growing around the edges.

At the corner point
 Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 29 S	T 29 S
<u>S 13</u>	R 3 W
S 24	S 18
R 4 W	
1964	

- from which new bearing trees
- A Fir 8" dia., bears S.12°W., 62 lks. dist. mkd. T29S R4W S24 BT.
 - A Fir 6" dia., bears N.54½°W., 27 lks. dist. mkd. T29S R4W S13 BT.

Cor. Fd. and used in BLM resurvey by Roseberry and Jelley, under Group #'s 255, 701 and 938 - surveyed July 1967/Oct. 1977 - (DCSO records, Vol. 39 Page 15857)