

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION C C for secs. 12 & 13 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6389)

End of blazed line. (No other marks or evidence of an established corner.)
Marked a Laurel tree 15" dia., at the point of intersection with the Township line for the corner to Secs. 12 and 13.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13794) and (Vol. 33 Pg. 13876)

Point for the closing cor. of secs. 12 and 13, on the E. bdy. of T29S R4W, at proportionate distance in latitude; there is no remaining evidence of the original corner.
Set an iron post, 28" long 2½" dia., 23" in the ground, with brass cap mkd.

T 29 S	T 29 S
CC S 12	S 18
S 13	
R 4 W	R 3 W
1964	

from which

A Fir 38" dia., bears S.54¼°W., 72 lks. dist. mkd. T29S R4W S13 CC BT.

A Fir 6" dia., bears N.62½°W., 71 lks. dist. mkd. T29S R4W S12 CC BT.

Fd. ok by D.Edwards, March 1998 - M 128-43

Mark Smalley - For: Roseburg Resources - 9/2003 - C.S. File 65/48-20

Found - 1964 BLM IPBC (properly mkd)
38" Fir stump S.54½°W., 47.5.
12" Fir N.62½°W., 46.9.
New - 7" Fir S.82°W., 32.0 scribed "S13 BT"
16" Fir N.88½°W., 41.6 scribed "S13 BT"
7" Fir N.46°W., 20.1 scribed "S12 BT"