

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13795)

-----  
Point for the ¼ sec. cor. of sec. 12 only, on the E. bdy. of T29S R4W, at midpoint in latitude.

Set an iron post, 28" long, 2½" dia., 23" in the ground, with brass cap mkd.

T 29 S  
    ¼  
    S 12  
R 4 W  
    1964

from which

A Cedar 24" dia., bears S.33½°W., 98 lks. dist. mkd. ¼ S12 BT.

A Hemlock 18" dia., bears N.77½°W., 78 lks. dist. mkd. ¼ S12 BT.

Fd. ok by D.Edwards, March 1998 - M 128-43

Mark Smalley - For: Roseburg Resources - 9/2003 - C.S. File 65/48-21

-----  
Found - 1964 BLM IPBC (properly mkd)

33" Cedar S.33½°W., 64.7 healed.

New - 10" Cedar N.16°W., 25.2 scribed "¼ S BT"

10" Fir N.84°W., 39.0 scribed "¼ S BT"