

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 700566

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 7 only, T29-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6297)

Set ¼ sec. post, from which
A Maple 6" dia., bears N.30°W., 25 lks.
A Red Fir 36" dia., bears S.55°E., 16 lks.

GLO survey by W.H. Byars, Contract #376, dated Jan. 22, 1881 found all witness trees standing. - (DCSO records, Vol. 15 Page 6315)

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13795)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 29 S
¼
S 7
R 3 W
1964

from which

A Cedar 17" dia., bears N.62½°E., 85 lks. dist. mkd. ¼ S7 BT.

A Fir 7" dia., bears S.36°E., 54 lks. dist. mkd. ¼ S7 BT

Fd. ok by D.Edwards, March 1998 - M 128-43