

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION C C for secs. 1 & 12 only (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6390)

Intersect township line 23.10 chs. South of established corner to secs. 1, 12, 6 and 17.
Marked a Fir tree, 6" dia., for the corner to secs. 1 and 12.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #554 - Surveyed July 1964/April 1965 - (DCSO records Vol. 33 Page(s) 13795-96)

Point for the closing cor. of secs. 1 and 12, on the E. bdy. of T29S R4W, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 28" long, 2½" dia., 22" in the ground, with brass cap mkd. T 29 S T 29 S

C C $\frac{S 1}{S 12}$ S 7
R 4 W R 3 W
1964

from which

A Fir 9" dia., bears S.21°W., 139 lks. dist. mkd. T29S R4W S12 CC BT.

A Fir 42" dia., bears N.56½°W., 447 lks. dist., mkd. T29S R4W S1 CC BT.

Fd. ok by D.Edwards, March 1998 - M 128-43