

TOWNSHIP 29 RANGE 05E POINT IDENTIFIER # 167573

PRIMARY CORNER DESCRIPTION NW Cor. Monument Crater Lake Nat'l Park

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey of the Boundaries of Crater Lake National Park by Carl R. Caudle, Examiner of Surveys, under Special Instruction dated June 1, 1903, Surveyed July/Sept 1903 - (DCSO records C.S. File 65/27-3 (AZ))

Set a lava stone 38x24x24" 26" in the ground for NW Cor. of Crater Lake National Park, marked
P L 13 M 39.62 chs. on N E
N W COR C L N P on S E
P L 18 M 32.49 chs. on S W
P L 1903 on NW faces from which
 A fir 31" dia., bears N.65°14'(?); 65 lks marked P L 13 M 39.62 chs BT
 A fir 43" dia., bears S.62°17'E., 22 lks marked N W COR C L N P BT
 A fir 33" dia., bears S.27°56'W., 42 lks marked P L 18 M 32.49 chs BT.
 A fir 37" dia., bears N.38°45'W., 113½ lks marked P L 1903 BT.
This cor. stands on a steep slope facing N in heavy fir timber.

GLO survey by Herbert N Raymond USCE, under Special Instr. dated March 22, 1930, Group No. 138; surveyed July/Oct. 1930 - (DCSO records C.S. File 65/27-3 O)

The NW cor. monument, constructed by the US Geological Survey (DCSO does not have this survey) in 1909, which is a concrete monument, 1 ft. sq. at the top, 3 ft. high, with a flat base, 3 ft. sq, and an iron post, 3" dia., set in the center, with the brass cap mkd. Crater Lake National Park, General Land Office, No. 39, and witnessed as described in the field notes of the 1903 survey of the Crater Lake Park Boundary.