

TOWNSHIP 29 RANGE 05E POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond USCE, under Special Instr. dated March 22, 1930, Group No. 138; surveyed July/Oct. 1930 - (DCSO records C.S. File 65/27-3 (AG))

-----  
Set an iron post, 3 ft. long, 1" dia., 30" in the ground, for 1/4 sec. cor., with brass cap marked

1/4  
S 6 | S 5  
1930

from which

- A fir, 11" dia., bears S.73°E., 44 lks., mkd: 1/4 S5 BT.
- A fir, 12" dia., bears S.10 1/2°W., 33 lks., mkd: 1/4 S6 BT.

BLM Dependent resurvey by Daniel Weller, Stephan Barott, & Harold Center under Group No. 1571, surveyed Sept. 1990/July 1992 - (DCSO records Vol. 51 Page(s) 19335-6)

-----  
The 1/4 sec. cor. of secs. 5 and 6, monumented with an iron post, 1" dia., firmly set, projecting 4" above ground, with brass cap mkd.

1/4  
S 6 | S 5  
1930

from which the remains of the original bearing trees

- A fir snag, 18" dia., bears S.73°E., 44 lks., with healed blaze.
- A fir, 20" dia., bears S.10 1/2°W., 33 lks., with healed blaze.

and a new bearing tree

- A fir, 13" dia., bears S.87°E., 23 1/2 lks., mkd. 1/4 S5 BT.

The geographic position (NAD 1927)

Latitude 43°04'34.81"N. Longitude 122°15'42.08"W.

From this point, the BLM, Control Station No. EC 41083, at Latitude 43°04'14.314"N. and Longitude 122°15'40.909"W. (NAD 1927), established in 1991 and determined by NAVSTAR Global Positioning System, bears S.2°24'13"E., 31.464 chs. (mean bearing and sea level distance); monumented with a PVC pipe, 6" dia., firmly set, projecting 28" above ground, supported in a mound of stone and concrete, 5 ft. base, 3 ft. high, with aluminum cap, 3" dia., set in center of PVC pipe, mkd. EC 41083 GPS 1991 and a triangle.