

TOWNSHIP 29 RANGE 05E POINT IDENTIFIER # 240573

PRIMARY CORNER DESCRIPTION ¼ Cor. Sec. 8(S) on 1930 N BDY C L N P

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Herbert N Raymond USCE, under Special Instr. dated March 22, 1930, Group No. 138; surveyed July/Oct. 1930 - (DCSO records C.S. File 65/27-3 P)

-----  
Set an iron post, 3 ft. long, 1" dia., 30" in the ground, for ¼ sec. cor., of sec. 8 only, with brass cap marked

¼ S 8  
1930

from which

A fir, 8" dia., bears N.40°E., 27 lks., mkd: ¼ S8 BT.

A fir, 9" dia., bears N.78°W., 61 lks., mkd: ¼ S8 BT.

BLM Dependent resurvey by Daniel Weller, Stephan Barott, & Harold Center under Group No. 1571, surveyed Sept. 1990/July 1992 - (DCSO records Vol. 51 Page(s) 19336)

-----  
The ¼ sec. cor. of sec. 8 only, on the Original North Boundary of Crater Lake National Park, monumented with an iron post, 1" dia., firmly set, projecting 6" above ground, with brass cap mkd.

¼ S 8  
1930

from which the original bearing trees

A fir, 22" dia., bears N.42°E., 27 lks., with healed blaze. (Record, N.40°E.)

A fir, 21" dia., bears N.73¾°W., 60 lks., with healed blaze. (Record, N.78°W., 61 lks.)