

TOWNSHIP 29 RANGE 05E POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond USCE, under Special Instr. dated March 22, 1930, Group No. 138; surveyed July/Oct. 1930 - (DCSO records C.S. File 65/27-3 AO)

-----  
Set an iron post, 3 ft. long, 1" dia., 30" in the ground, for 1/4 sec. cor., with brass cap marked

1/4  $\frac{S\ 5}{S\ 8}$   
1930

from which

- A larch, 13" dia., bears N.14°E., 47 lks., mkd: 1/4 S5 BT.
- A fir, 9" dia., bears S.54°W., 66 lks., mkd: 1/4 S8 BT.

BLM Dependent resurvey by Daniel Weller, Stephan Barott, & Harold Center under Group No. 1571, surveyed Sept. 1990/July 1992 - (DCSO records Vol. 51 Page(s) 19334)

-----  
The 1/4 sec. cor. of secs. 5 & 8, monumented with an iron post, 1" dia., firmly set, projecting 8" above ground, with brass cap mkd.

1/4  $\frac{S\ 5}{S\ 8}$   
1930

from which the original bearing trees

- A larch, 19" dia., bears N.14°E., 47 lks., with healed blaze.
- A fir, 23" dia., bears S.54°W., 66 lks., with healed blaze.