

TOWNSHIP 29 RANGE 05E POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION Cor. Secs. 5; & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond USCE, under Special Instr. dated March 22, 1930, Group No. 138; surveyed July/Oct. 1930 - (DCSO records C.S. File 65/27-3(y))

Set an iron post 3 ft. long, 1" dia., 30" in the ground, for ¼ sec. cor., with brass cap mkd:

¼ $\frac{S\ 32}{S\ 5}$
1930

from which

- A larch, 16" dia., bears S.20°W., 66 lks., mkd: ¼ S5 BT.
- A pine, 34" dia., bears N.33½°W., 29 lks., mkd: ¼ S32 BT.

BLM Dependent resurvey by Daniel Weller, Stephan Barott, & Harold Center under Group No. 1571, surveyed Sept. 1990/July 1992 - (DCSO records Vol. 51 Page(s) 19334-5)

The ¼ sec. cor. of secs. 5 and 32 on the N. bdy. of the Tp., monumented with an iron post, 1" dia., firmly set, projecting 3" above ground, with brass cap mkd.

¼ $\frac{S\ 32}{S\ 5}$
1930

from which the remains of the original bearing trees

- A larch, 18" dia., bears S.20°W., 66 lks., with healed blaze.
 - A fir snag, 32" dia., bears N.29°W., 28 lks., with scribe marks ¼ S32 BT visible on partially healed blaze. (Rec. pine, N.33½°W., 29 lks.)
- and a new bearing tree
- A fir, 9" dia., bears N.9¾°E., 51 lks., mkd. ¼ S32 BT.