

TOWNSHIP 29 RANGE 05E POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond USCE, under Special Instr. dated March 22, 1930, Group No. 138; surveyed July/Oct. 1930 - (DCSO records C.S. File 65/27-3 (AM-AN))

Set an iron post, 3 ft. long, 1" dia., 32" in the ground, for 1/4 sec. cor., with brass cap marked

1/4
S 5 | S 4
1930

from which

- A fir, 9" dia., bears N.86°E., 21 lks., mkd: 1/4 S4 BT.
- A pine, 22" dia., bears S.46°W., 32 lks., mkd: 1/4 S5 BT.

BLM Dependent resurvey by Daniel Weller, Stephan Barott, & Harold Center under Group No. 1571, surveyed Sept. 1990/July 1992 - (DCSO records Vol. 51 Page(s) 19333)

The 1/4 sec. cor. of secs. 4 and 5, monumented with an iron post, 1" dia., firmly set, projecting 6 ins. above ground, with brass cap mkd.

1/4
S 5 | S 4
1930

from which the remains of the original bearing trees

- A fir, 13" dia., bears N.86°E., 21 lks., with healed blaze.
 - A root hole, bears S.46°W., 32 lks., alongside of which is a dead and down pine, size indeterminate, with scribe marks 1/4 S5 BT visible on partially healed blaze.
- and a new bearing tree
- A fir, 8" dia., bears N.12°W., 29 lks., mkd. 1/4 S5 BT.