

TOWNSHIP 29 RANGE 5E POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond USCE, under Special Instr. dated March 22, 1930, Group No. 138; surveyed July/Oct. 1930 - (DCSO records C.S. File 65/27-3 AP)

Set an iron post, 3 ft. long, 1" dia., 30" in the ground, for 1/4 sec. cor., with brass cap marked

1/4
S 4 | S 3
1930

from which

- A pine, 6" dia., bears S.38 1/2°E., 26 lks., mkd: 1/4 S3 BT.
- A pine, 6" dia., bears S.87°W., 45 lks., mkd: 1/4 S4 BT.

BLM Dependent resurvey by Daniel Weller, Stephan Barott, & Harold Center under Group No. 1571, surveyed Sept. 1990/July 1992 - (DCSO records Vol. 51 Page(s) 19331)

The 1/4 sec. cor. of secs. 3 & 4, monumented with an iron post, 1" dia., firmly set, projecting 8" above ground, with brass cap mkd.

1/4
S 4 | S 3
1930

from which the original bearing trees

- A pine, 8" dia., bears S.38 1/2°E., 26 lks., with scribe marks 1/4 S3 BT visible on partially healed blaze.
- A pine, 10" dia., bears S.87°W., 45 lks., with scribe marks 1/4 S4 BT visible on partially healed blaze.