

TOWNSHIP 29 RANGE 05E POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4; 33 & 34 T28-5E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond USCE, under Special Instr. dated March 22, 1930, Group No. 138; surveyed July/Oct. 1930 - (DCSO records C.S. File 65/27-3 (AA))

-----  
Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for cor. of secs. 3, 4, 33, & 34, with brass cap mkd:

T28S R5E  
S 33|S 34  
S 4|S 5  
T29S  
1930

from which

- A pine, 6" dia., bears N.32°E., 18 lks., mkd: T28S R5E S34 BT.
- A pine, 7" dia., bears S.75°E., 21 lks., mkd: T29S R5E S3 BT.
- A pine, 6" dia., bears S.51°W., 23 lks., mkd: T29S R5E S4 BT.
- A pine, 6" dia., bears N.9½°W., 28 lks., mkd: T28S R5E S33 BT.

BLM Dependent resurvey by Daniel Weller, Stephan Barott, & Harold Center under Group No. 1571, surveyed Sept. 1990/July 1992 - (DCSO records Vol. 51 Page(s) 19332)

-----  
The cor. of secs. 3, 4, 33, & 34, on the N. bdy. of the Tp., monumented with an iron post, 2" dia. firmly set, projecting 7" above ground, with brass cap mkd.

T28S R5E  
S 33|S 34  
S 4|S 3  
1930

from which the original bearing trees

- A pine, 10" dia., bears N.32°E., 18 lks., with scribe marks 28S R5E S34 B visible on partially healed blaze.
- A pine, 11" dia., bears S.75°E., 21 lks., with scribe marks S R5E S3 BT visible on partially healed blaze.
- A pine, 11" dia., bears S.51°W., 23 lks., with scribe marks T29S R5E S4 BT visible on partially healed blaze.
- A pine, 11" dia., bears N.9½°W., 28 lks., with scribe marks T28S R5E S33 BT visible on partially healed blaze.