

TOWNSHIP 29 RANGE 05E POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3; & 34 T28-5E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond USCE, under Special Instr. dated March 22, 1930, Group No. 138; surveyed July/Oct. 1930 - (DCSO records C.S. File 65/27-3 (AB))

Set an iron post, 3 ft. long, 1" dia., 30" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S\ 34}{S\ 3}$
1930

from which

- A pine, 6" dia., bears S.3°W., 4 lks., mkd: 1/4 S3 BT.
- A pine, 8" dia., bears N.44°W., 81 lks., mkd: 1/4 S34 BT.

BLM Dependent resurvey by Daniel Weller, Stephan Barott, & Harold Center under Group No. 1571, surveyed Sept. 1990/July 1992 - (DCSO records Vol. 51 Page(s) 19331)

The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 1" dia., firmly set, projecting 9" above ground, with brass cap mkd.

1/4 $\frac{S\ 34}{S\ 3}$
1930

from which the original bearing trees

- A pine, 9" dia., bears S.3°W., 4 lks., with healed blaze.
- A pine, 11" dia., bears N.44°W., 81 lks., with scribe marks 1/4 S34 BT visible on partially healed blaze.

The corner is located 30 lks. south of Forest Service Road No. 281, 15 lks. wide, bears N.70°E. and S.70°W.