

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 34, & 35 T28-5E

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Herbert N Raymond USCE, under Special Instr. dated March 22, 1930, Group No. 138; surveyed July/Oct. 1930 - (DCSO records C.S. File 65/27-3 (AB))

Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for cor. of secs. 2, 3, 34, & 35, with brass cap mkd:

T28S R5E
S 34 | S 35
S 3 | S 2
T29S
1930

from which

- A pine, 7" dia., bears N.72°E., 19 lks., mkd: T28S R5E S35 BT.
- A pine, 5" dia., bears S.48°E., 16 lks., mkd: T29S R5E S2 BT.
- A pine, 6" dia., bears S.51°W., 57 lks., mkd: T29S R5E S3 BT.
- A pine, 8" dia., bears N.49°W., 62 lks., mkd: T28S R5E S34 BT.

BLM Dependent resurvey by Daniel Weller, Stephan Barott, & Harold Center under Group No. 1571, surveyed Sept. 1990/July 1992 - (DCSO records Vol. 51 Page(s) 19330)

The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., monumented with an iron post, 2" dia., firmly set, projecting 4" above ground, with brass cap mkd.

T28S R5E
S 34 | S 35
S 3 | S 2
T29S
1930

from which the remains of the original bearing trees

- A pine, 9" dia., bears S.48°E., 16 lks., with scribe marks T29S R5E S2 BT visible on partially healed blaze.
- A pine snag, 8" dia., bears S.51°W., 57 lks., with scribe marks T29S R5E S3 BT visible on partially healed blaze.
- A pine, 11" dia., bears N.49°W., 62 lks., with scribe marks T28S R5E S34 BT visible on partially healed blaze.

and new bearing trees

- A pine, 12" dia., bears N.37¾°E., 41 lks., mkd. T28S R5E S35 BT.
- A pine, 11" dia., bears S.57°W., 16 lks., mkd. T29S R5E S3 BT.