

TOWNSHIP 29 RANGE 05E POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 12, 11, & 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond USCE, under Special Instr. dated March 22, 1930, Group No. 138; surveyed July/Oct. 1930 - (DCSO records C.S. File 65/27-3 AU)

-----  
Set an iron post, 3 ft. long, 2" dia., 30" in the ground, for cor. of secs. 1, 2, 11, & 12, with brass cap mkd:

T29S R5E  
S 2 | S 1  
S 11 | S 12  
1930

from which

- A pine, 9" dia., bears N.7°E., 45 lks., mkd: T29S R5E S1 BT.
- A pine, 12" dia., bears S.40½°E., 112 lks., mkd: T29S R5E S12 BT.
- A pine, 18" dia., bears S.37°45'W., 106 lks., mkd: T29S R5E S11 BT.
- A pine, 8" dia., bears N.69°W., 9 lks., mkd: T29S R5E S2 BT.