

TOWNSHIP 29 RANGE 05E POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 12; 6 & 7 T29 R6E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond USCE, under Special Instr. dated March 22, 1930, Group No. 138; surveyed July/Oct. 1930 - (DCSO records C.S. File 65/27-3 (AE))

-----  
Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 1, 6, 7, & 12, with brass cap mkd:

T29S  
R5E R6E  
S 1 | S 6  
S 12 | S 7  
1930

from which

- A fir, 9" dia., bears N.74°E., 63 lks., mkd: T29S R6E S6  
BT.
- A pine, 13" dia., bears S.10°E., 46 lks., mkd: T29S R6E S7  
BT.
- A fir, 16" dia., bears S.35°W., 23 lks., mkd: T29S R5E S12  
BT.
- A fir, 18" dia., bears N.85°W., 38 lks., mkd: T29S R5E S1  
BT.