

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 041020

PRIMARY CORNER DESCRIPTION NW Cor. J. Adams DLC #41

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original DLC survey by Burnett & Bowman under Contract date 1855. (D.L.C. Records Book, page 543)

A B. Oak 10" dia., marked for NW. cor. of C 41

Douglas Co. Surveyors Office - H.L. Eppstein, Co. Surveyor - B.A. Lane - N.E. Richardson - J.T. Black -9/16-30/29 - Vol. 3 Pg 293 - "Old" Cor. Book Pg. 128

A Black Oak tree was corner. This tree showed ax marks in hole in tree. J.T. Black said he had seen scribe marks on tree. Set post at foot of tree for corner & mkd:
A 8" Fir, S.88°E., 11 lks.

Douglas Co. Surveyors Office - James W. Byron, Deputy -3-1-62 - (Per hand written note by James W. Byron in the "Douglas Co. Surveyor's Record of Government Corner's Renewed")

Drove 3/4" I.R. at cor. tree.

Fd. OK by R. Brown, June 1998 - M129-5

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 8/12/1999 - C.S. File 66/12-33

Found - 10" now 17" dia., B.Oak with a previously opened hole & 3/4" I.R. from 1962, set near center. (Orig. cor. tree)
8" now 23" dia., D.Fir with a fully healed single blaze, bears S.88°E., 7.3 ft. (agrees with rec.) 1929
New BOs- 2½" angle iron braced fence post set in concrete bears S.12°E., 3.3 ft.
30" dia., 1½ ft. high solid D.Fir stump, set a 6" long nail through BT tag on top at center, nail bears S.39°W., 12.2 ft.
5" dia., Maple double blazed & scribed "NW DLC 41 CS BT" bears S.65°W., 24.8 ft.