

PRIMARY CORNER DESCRIPTION SW Cor. H. Adams, DLC #42

Alias 043060 Description SE Cor. Maloney, DLC #43
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original DLC survey by Burnett & Bowman under Contract date 1855. (D.L.C. Records Book, page(s) 544 & 545)

Set a post on line between Secs. 32 & 33, 10.96 chs N of Sec. Cor. marked, from which
 A W. Oak 12" dia., bears N.82½°E., 768 lks.

ON CLAIM #43
A post marked, a quadrangular trench & stone in the center.

Doug. County Surveyors Office - Karen Reed - S.J. Flause - Jan. 2, 1979 - C.S. File 60/24-3

Found - An orig. 16"x12"x10" sandstone marked "42" on top.
 A 3/4" I. Pipe bears North 15" from center of stone.
Set - A 1"x36" I. Pipe with brass cap on cardinal direction of S. 82' from SW cor. of DLC Mkd:
 "Douglas County Surveyor" Wit. Cor.
 SW Cor. | T29S
 DLC 42 | R5W
 N. 82 ft.
 1979
New BTs -A 13" Ash bears N.78°E., 107.5' dist., bark scribed "WC SW DLC 42 CS BT"
 A 16" Ash bears S.48°E., 142.5' dist. barked scribe "WC SW DLC 42 CS BT"
Note - SW cor. lies in path of future drainage ditch.
 Public Works request. To preserve SW Cor. DLC 42, T29S R5W.

Doug. County Surveyors Office - Randall Smith - Stephen Flause - Oct. 10, 1985 - C.S. File 62/29-11

Found - An original stone first noted in the orig. survey notes of DLC #43 and first described as a 12"x16" stone, marked DLC 42 in the unrecorded Gray Acres Plat, C.S. 50/56, is now a broken but firmly set stone, marked with a 4 and a 2, partially broken off. Stone measures 8"x8"x14".
A 3/4" iron pipe firmly set but leaning SW'ly bears North approx. 1.3' (Rec. North 1.6') C.S. 50/56
A 3/4" iron pipe firmly set but leaning S. At its plumb position, it bears N. 110.2'. C.S. 50/56
3/4"x 3/4" angle iron firmly set and protruding 6" from the ground bears West, 226.9' (Rec. S.89°57'W., 227.2') M 9-43

(Cont. Next Page)

1

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 042030

PRIMARY CORNER DESCRIPTION WC SW Cor. H. Adams, DLC #42

Alias 043060 Description SE Cor. Maloney, DLC #43

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

New - A DCSO brass cap on an iron pipe set flush with ground bears South 82.0'. 1979 renewal (WC).
A 5/8" iron rod with a plastic cap marked LS 866 protrudes 5" above ground and bears N.46¼°W., 44.0'. M 99-10
An unrecorded 3/4" iron pipe protruding 1' above ground bears S.2¼°E., 38.6'.
A 5" DBH O. Ash bark scribed SW DLC 42 CS BT, bears N.72½°W., 18.0'.
Note - On east edge of drainage ditch at intersection of ditches from east and southeast approx. 500' west of the south end (point where road turns due east) of Weeks Road.

Fd. Stone & I.P. By W. Ruppert 7/91, M 112-32.
Fd. Stone & I.P. By W. Ruppert 3/93, 1993-0040.
Fd. OK by R.Brown, June 1998 - M129-5
Fd. BC by Aron J. Cutsforth 9/2007 - St. Hwy 99-005E
FD. BC by Aron J. Cutsforth 1/2009 - M158-49