

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 046060

PRIMARY CORNER DESCRIPTION SE Cor. Cornelison DLC # 46

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original DLC survey by Burnett & Bowman under Contract date 1855. (D.L.C. Records Book, page(s) 551)

Set post SE cor, from which;
A Fir, 36" dia., bears N.25°W., 35 lks.
An Oak, 12" dia., bears N.15°E., 60 lks.

Douglas Co. Surveyors Office - H.L. Eppstein, Co. Surveyor - W.S. Crear - Geo. Spam - Dec. 18, 1925 - "Old" Cor. Book Page 127 - (Could find no other record source)

Set this corner by running from NE and SW corners of claim to SE corner of claim. The distance & bearing at corner found two trees which checks out as old BTs but burnt out so set 4"x4"x4' stake and mkd. new BT
Fir, 30" dia., S.10°15'W., 21.0'.

Douglas Co. Surveyors Office - James W. Byron, Co. Surveyor - John M. Powell & Crew - April 1969 - C.S. File 54/84 - M 37-44

This corner set from survey at pro-rated dist.
Set - Brass cap at cor. mkd: County Surveyor's Office 1969 T29S R5W SE Cor DLC # 46 S 35
New BTs- 13" D. Fir, S.79°W., 38.5' mkd: "SE DLC 46 CS BT"
8" D. Fir, N.8°E., 12.1' mkd: "SE DLC #46 CS BT"

Fd. OK by Bentz, July 1995 - M124-5