

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 050010

PRIMARY CORNER DESCRIPTION NNW Cor. Carson DLC #50

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Original DLC survey by Burnett & Bowman under Contract date 1855. (D.L.C. Records Book, page(s) 532)

Set a post from which;
A W. Oak, 6" dia., bears S.15°W., 28 lks.
A B. Oak, 20" dia. bears S.43½°W., 34 lks.

Douglas Co. Surveyors Office - C.E. Roberts, Co. Surveyor - Aug. 1903 - FB 7 Page 12(23) - "Old" Cor. Book Page 128

Set Cedar post & mkd:
Black Oak 12" dia., S.85°E., 108 lks.

John H. Markham, Jr. - For: Umpqua Plywood Corp. - May 15, 1956 - C.S. File 42/189

Point for corner determined by OBTs:
A 16" W.O. stump bears S.15°W., 18.5', OBT, found scribe.
An 18" B.O. stump bears S.85°E., 23.5', OBT, found scribe.
Set - 1"x24" iron pipe at corner point, from which;
5" W.O. bears S.13°W., 20.0' mkd: CL. 50 BT
6" La. bears N.79°E., 26.0' mkd: CL. 50 BT
10" La. bears S.48°E., 43.0' mkd: CL 50 BT
Old fence corner bears S.45°E., 22.5'. Fence runs S & E.
C.O.P. Co. transmission tower bears N.55°W., approx. 330'.

Fd. Ok by K.DeGroot, July 1997 - M124-60