

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor 6 & 7; 1 & 12 of T29-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6419)

Set post of cor. to secs. 1, 12, 6, & 7, from which,
B. Oak, 8" dia., bears S.55°E., 21 lks.
Laurel, 18" dia., bears N.87°E., 100 lks.
W. Oak, 12" dia., bears N.89°W., 35 lks.
B. Oak, 20" dia., bears S.51°W., 250 lks.

James W. Byron, Deputy Co. Surveyor - Dale McFarland and John Powell - Feb. 1962 - C.S. File 49/64-56

Found - Orig. 8", now 14" B. Oak S.55°E. 13.9', previously opened, shows good reverse scribing on old chip "R".
Orig. 18", now 36" Laurel snag, N.87°E. 66'.
Orig. 12", now 20" W. Oak N.89°W. 23.1', shows scars. We do not open.
Orig. S.W. BT not found.

Set brass cap mkd: County Surveyors R6 $\frac{S\ 1}{S\ 12}$ | $\frac{S\ 6}{S\ 7}$ T29S R5

New BTs - 8" W.Oak bears S.79°W. 52.0' scribed S12 T29S R6W CS BT.
11" W.Oak bears N.58°E. 74.5' scribed S6 T29S R5W CS BT.
10" W.Oak bears S.69°E. 18.0' scribed S7 T29S R5W CS BT.

Fence corner is N.89°W. 21.3' from monument.

Fd. OK, Aug. 1990, M 110-60
Fd. Ok by R. Brown, 1/1997, M 124-38 A & B.
Fd. OK by R. Brown, 6/2001, M 138-38

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 1/13/2009 - C.S. File 67/28-5

Found - 2½" brass cap on a 1½" O.D. iron pipe protruding 13" out of ground. (1962)
Orig. NW BT now down, all others are gone.
1962 SW BT now gone.
10" now 10" dia., 6' high rotted W.Oak snag a rotted blaze bears S.69°E., 18.0 ft. 1962
11" now 20" dia., W.Oak with a fully healed double blaze, bears N.56°E., 74.5 ft. (Rec. N.58°E., 74.5 ft.) 1962

continued next page

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor 6 & 7; 1 & 12 of T29-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New - Double trunked W.Oak, double blazed & scribed "T29S R6W S12 CS BT" on 10" dia., Easterly trunk bears S.7°W., 72.7 ft. to center of root crown
5" Pine, double blazed & scribed "X BT" bears S.74°W., 45.4 ft.
Double trunked cedar double blazed & scribed "X BT" on 5" dia., easterly trunk bears N.65°W., 45.7 ft

Note - Compass decl. 16½°E.