TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6446)

Set ¼ sec. post at average dist., from which;
A R. Fir 36" dia., bears S.15°E., 185 lks.
A Pine, 8" dia., bears N.27°E., 68 lks.

Douglas Co. Surveyors Office - Ben B. Irving, Deputy - Witnesses: H.C. Baird & F.E Weaver - 8/21/29 - C.S. 1/65B - M 1-61 - "Old" Cor. Book Page 127 - Vol. 3 Pg 294

Renewed by setting a serpenteen rock 6"x8" with X chisled on top & ¼ S. on S face. Position identified from one orig. BT:
40" Fir, S.15°E., 185 lks
New BTs- 8" Fir, S.28°50'W., 11 lks. mkd: ¼ S31 CS BT
8" Fir N.2°20'E., 54 lks. mkd: ¼ S30 CS BT

Douglas Co. Surveyors Office - James W. Byron, Deputy - Dale McFarland - John Powell - March 1962 - C.S. File 49/64-79

Found - Both BTs as recorded by B.B.I. except distances are transposed. Should be 8" Fir S.28°50'W., 54 lks. & 8" Fir N.2°20'E., 11 lks. Stone set for corner, now broken into small parts.
Set - Brass cap at cor. mkd: County Surveyor's Office, 1962 ¼ S30/S31 T29S R5W
Note - E - W fence is 1.0' South of corner.

Found OK by K. DeGroot, Jan. 2001 - M136-32