

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6447)

Set 1/4 sec. post at average dist., from which;
A Pine, 36" dia., bears N.2°W., 75 lks.
A Pine, 24" dia., bears S.5°W., 155 lks.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Dale McFarland - John Powell - Feb. 1962 - C.S. 49/64-66

Found - Orig. 24", now 36" Pine stump S.5°W., 102.3'. We open & find good scribing "1/4S".
Orig. N.W. BT now Pine stump, face burned.
Found mound of stone at corner.

Note - Corner is on top of high North-South ridge & 20' West of log. road.

Set - Brass cap at cor. mkd:
County Surveyor's 1/4 S19 T29S R5W
Office 1962 S30

New BTs- 20" Pine, bears S.47 1/2°W., 142.9' scribed 1/4 S30 CS BT
7" Cedar bears S.10 1/2°W., 150.9' scribed 1/4 S30 CS BT

Douglas Co. Surveyors Office - Randall Smith, Deputy - Stephen Flause - Jan. 17, 1990 - C.S. File 64/5-3

Found - A 1962 DCSO 2 1/2" dia., brass cap on a 1 3/8" O.D. x 36" long iron pipe is found out of the ground.
36" now 24" dia., 3' high Ponderosa Pine stump, no blazes or marks visible, bears N.3 3/4°W., 50.4' (rec. N.2°W., 49.5' dist. is a possible face meas.) Orig. BT

Orig. 24" SW Pine is gone, probably scraped out by cat work.

20" now 27" dia., Ponderosa Pine with a fully healed double blaze bears S.46 1/2°W., 142.9' (rec. S.47 1/2°W., 142.9'). 1962 renewal.

7" now 25" dia., 2 1/2' high cedar stump, evidence of blaze visible bears S.9 3/4°W., 150.9' (rec. S.10 1/2°W., 150.9'). 1962 renewal.

Set - Reset 1962 DCSO BC/IP at point determined from intersecting distances from BTs (see accessories found). The marks "RESET 1990" are added to brass cap. BC/IP now protrudes 6" above ground, and is surrounded by a 2' dia., mound of stone.

New BTs- 15" dia., Jeff. Pine, double blazed & scribed "1/4 S19 CS BT" bears N.17 1/4°E., 108.6'.

16" dia., Ponderosa Pine double blazed & scribed "1/4 S19 CS BT bears N.57 1/2°W., 65.8' (Cont. Next Page)

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Corner lies on top of a North-South ridge, approx. 20' West of a dirt road. A metal wit. post and sign is set 2' east of corner.

Found OK by K. DeGroot, Jan. 2001 - M136-32