

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6451)

Set ¼ sec. post at aver. dist., from which;
An Ash, 6" dia, bears S.27°E., 93 lks.
A B. Oak, 8" dia., bears N.60°E., 24 lks.

Wm. S. Barnes - For: Otis Clayton - Nov. 1969 - C.S. File 55/136 - M 33-63

Prorated ¼ cor.
Set - Brass cap mkd: Eng. No. 2128, Nov. 1969, ¼ Cor. 6/7 T29S R5W.
BTs - 26" Oak, N.34°W., 263.8' mkd: ¼ S 6 BT.
30" Oak, S.11°W., 111.3' mkd: ¼ S 7 BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 1/8/2009 - C.S. File 67/28-3

Found - 2½" brass cap n a 1½" O.D. iron protrudes 12" out of ground (1969)
26" now 30" dia., W.Oak with a fully healed double blaze bears N.34°W., 264.4 ft. (rec. N.34°W., 263.8 ft.) 1969
SW BT gone.
New - 38" dia., W.Oak double blazed & scribed "¼ S6 CS BT" bears S.41°E., 220.6 ft.
9" dia., W.Oak, double blazed & scribed "¼ S7 CS BT" bears S.80½°E., 149.6 ft.
Note - SE cor. of feed shed bars N.47°W., 83' Compass decl. 16½°E.