

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6445)

Set a post from which;
A B. Oak, 18" dia., bears S.15°E., 23 lks.
A B. Oak, 30" dia., bears N.60°W., 69 lks.

Douglas Co. Surveyors Office - Ben B. Irving, Deputy -
Witnesses: H.C. Baird - F.E. Weaver - 8/21/29 - Vol. 3 Pg 294
- M 1-61 - "Old" Cor. Book Page 128

Conglomerate rock mkd. with "X", set from orig. BTs which I
remark.
White Oak, 36" dia., N.60°W., 69 lks. ¼ S31 CS BT.
White Oak, 30" dia., S.15°E., 23 lks. ¼ S32 CS BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Dale
McFarland - John Powell - Feb. 1962 - C.S. File 49/64-67

Found - Both BTs as recorded by BBI in 1929. NW BT down &
rotted, shows old axe marks. SE BT shows good
scar & it is Black Oak not White Oak.
6"x2" (wedge shape) 3" above ground with + on S.
face, stone.
New BT - 8" W. Oak, bears N.59°W., 57.5' scribed ¼ S31 CS BT.
Note - Fence corner 14' south.

Fd Ok by Don Garret - Feb. 1973 - M 47-63

Douglas Co. Surveyors Office - Karen Reed - Pete Earle -
10/11/79 - C.S. File 60/34-18

Found - 12"x18"x22" conglomerate stone mkd: "¼" on South
face. (X was rec. previously, origin unknown)
1" I.P. x 30" I.P. buried 26" in the ground bears
East, 0.96' dist. from stone. (M 1-35)
An orig. 18" B. Oak, now 36" with well healed single
blaze bears S.15°E., 15.2'.
An orig. 30" B. Oak, now down & badly rotted bears
N.60°W., 45.5'.
An 8" W. Oak, now 10" with well healed double blaze
bears N.59°W., 57.5'.
Set - 1"x36" I. Pipe with brass cap stamped "Douglas
County Surveyor T29S R5W S31 S32 ¼ 1979" at cor.
position as determined from orig. 36" B. Oak. I
set fd. stone on north side of cap & I.P. on
south side of cap. (Cont. Next Page)

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BT - 28" dia., B. Oak scribed "¼ S31 CS BT" in a double blaze bears S.31°W., 54.1'.
Corner lies in a N-S fence 14' North of fence corner.

Douglas Co. Surveyors Office - Randall Smith, Deputy -
Stephen J. Flause - Terrie Franssen - 5/13/91 - C.S. 64/15-6

Found - 2½" dia., 1979 DCSO brass cap on a 1" O.D. I.P.,
protrudes 4" above ground.
A stone which top measures 10"x6" protrudes 4" above
ground "¼" is marked on south side, bears North
6" from BC/IP.
1" I.D. I.P. is found along southedge of BC/IP
protruding 4" above ground. M 1-35
18" now 38" dia., B. Oak with a fully healed single
blaze, bears S.20°E., 15.2' (Rec. S.15°E., 15.2')
Orig. BT.
Orig. NW BT now gone.
8" now 12" dia., W. Oak with a fully double blaze,
bears N.59°W., 57.5' (agrees w/rec.)
28" now 30" dia., B. Oak with an unhealed double
blaze, scribing visible "¼ S31 CS BT" bears
S.31°W., 54.1' (agrees w/rec).
New BT - 8" dia., W. Oak, double blazed & scribed "¼ S31 CS
BT" bears N.38°W., 58.8'.