

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6445)

Set a post for cor. to secs. 29, 30, 31, & 32 from which:
 A Laurel, 8" dia., bears N.50°E., 445 lks.
 A Pine, 30" dia., bears N.12°W., 225 lks.
 A B.Oak, 14" dia., bears S.88°E., 708 lks.

Alton E. Alspaugh - March 1947 - Subd. Plats Vol. 7 Pg 35A

Established. 3/4" iron pipe set 24" in ground with rock mound.

Douglas Co. Surveyors Office - Stephen J. Flaue - Terrie Franssen - June 1990 - C.S. File 64/9-14

Reported as not found.
 Found - A 3/4" I.D. iron pipe set in a 30" dia., 18" tall mound of stone; recorded in subdivision plat of the Edwin Weaver Estate (recorded in Douglas County records of Subdivisions Vol. 7 Page 35)
 No evidence of orig. corner monument is found.
 Several trees and stumps were opened in search of orig. bearing tree evidence. No orig. evidence was found.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flaue - 8/11/1999 - C.S. File 66/12-11

Found - 1 1/4" I.D. iron pipe protrudes 3" above ground with a 5/8" I.D. iron pipe extending from center of 1 1/4" IP protrudes 15" above ground all surrounded by a mound of stone. 1947
 30" now down & rotted 30" dia., Pine shows evidence of previous search, find old blaze and illegible curved scribe marks (probably a 2 or 3) bears N.12°W., 148.5 ft. (agree w/rec) OBT
 No evidence of other OBTs found.

Set - 2 1/2" dia., brass cap on a 1 1/2" O.D. by 32" long iron pipe is set at a position determined by found orig. BT. protrudes 6" above ground. Mkd:

DOUGLAS COUNTY SURVEYORS
 T29S
 S 30 | S 29 R
 S 31 | S 32 5
 1999 W
 OFFICE

continued next page

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>20" Pine single blazed & scribed "T29S R5W S30 BT CS" bears N.36°W., 147.5 ft. Iron pipe from 1947 bear S.24°E., 304.7 ft. 31" I.Cedar double blazed & scribed "T29S R5W S29 CS BT" bears N.63 3/4°E., 168.1 ft. 10" Pine double blazed & scribed "T29S R5W S32 CS BT" bears S.87°E., 185.6 ft.</p>
Found OK by K. DeGroot, Jan. 2001 - M136-32