

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6446-7)

Set a post for cor. to secs. 19, 20, 29 & 30, from which;
A B.Oak, 10" dia., bears S.5°E., 312 lks.
A W.Oak, 14" dia., bears N.65°E., 275 lks.
A B.Oak, 12" dia., bears N.50°W., 225 lks.
A Pine, 30" dia., bears S.10°W., 250 lks.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 8/23/1999 - C.S. File 66/12-14

Found - 14" now 29" dia., W.Oak with a hole showing evidence of being opened at least twice, once by axe and another time by chain saw. I open further & find reverse scribe mark "S", bears N.65°E., 181.5 ft. We rescribe high above opened blaze, approx. 3½ ft. above ground on a single blaze.

No other BTs found.

Set - 2 3/8" dia., brass cap on a 1 3/8" O.D. by 32" long brass cap is set at a position determined by orig. BT. protrudes 8" above ground, mkd:

DOUGLAS COUNTY SURVEYORS

T29S

R5W

S 19 | S 20

S 30 | S 29

1999

OFFICE

13" dia., D.Fir double blazed & scribed "T29S R5W S19 CS BT" bears N.78°W., 42.1 ft.

15" dia., D.Fir double blazed & scribed "T29S R5W S30 CS BT" bears S.76½°W., 42.3 ft.

12" dia., Cedar double blazed & scribed "T29S R5W S20 CS BT" bears N.26½°E., 123.0 ft.

Note - Easterly edge of pond bears N.9°W., approx. 300 ft. Metal wit. post & sign set 2 ft. North of corner.

Found OK by K. DeGroot, Jan. 2001 - M136-32

Fd. As per record, May 2019 by D. Edwards M175-54