

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6449)

-----  
Set a post for ¼ sec. corner, from which;  
A W. Oak, 12" dia., bears S.45°E., 110 lks.  
A B. Oak, 8" dia., bears N.18°E., 80 lks.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Ray Irving - John Fee - 11/22/54 - C.S. File 46/63 PG 2

-----  
Found - Both orig. BTs. SE BT checks for bearing & dist.  
The recorded NE BT (N.18°E., 80 lks) found to be N.18°W., 80 lks.  
The SE BT scribed ¼ BT. The NW BT has rotted center.  
No scribing visible.

Set - 1" iron pipe with brass cap for cor. mkd: County Surveyors Office, T29S R5W 1954 ¼ sec 18|17, on east west fence line.

BTs - 22" B.O., S.41°E., 77.8', mkd: ¼ S17 CS BT  
24" B.O. N.25°W., 47.6', mkd: ¼ S18 CS BT

Fd Ok by G. Lang - 12/2006 - 2007-0004 A&B