

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6450)

-----  
Set ¼ sec. cor. post, from which;  
A B. Oak, 8" dia., bears S.73°E., 67 lks.  
A B. Oak, 30" dia., bears N.35°W., 44 lks.

Douglas Co. Surveyors Office - H.L. Eppstein, Co. Surveyor - W.S. Crear - Geo. Findley - 3/27/26 - C.S. File 3/52 - Vol. 3 Pg 266 - "Old" Cor. Book Pg 127

-----  
Set corner from 30" Black Oak (old BT) which bears SE.  
Set - 3"x3"x3' Oak stake & mkd: one new BT  
A 15" White Oak N.60°W., 27.4'

Douglas Co. Surveyors Office - James W. Byron, Deputy - Dale McFarland - John Powell - 3/62 - C.S. 49/64-70

-----  
Found - Now 20" W. O. N.60°W., 27.4' show good scribing "¼S"  
Also find orig. SE BT, now down.  
Set - Brass Cap at cor. mkd: County Surveyor's Office 1962  
¼ S7 | S8 T29S R5W  
New BT - 8" W. Oak, bears N.42°E., 18.2' scribed ¼ S8 CS BT.  
Note - Corner is at intersection of a N-S fence and a westerly fence. (See sketch in C.S. File 49/64)

Fd. brass cap by R. Brown, Sept. 2006/June 2007 - RM 4-14

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 10/12/2009 - C.S. File 67/28-39

-----  
Found - 2½" brass cap on a 1½" O.D. iron pipe extends 18" out of ground (properly marked). 1962  
No OBTs Fd.  
15" now root hole, bears N.60°W., 27.4 ft. 1926  
8" now 8" dia., down W.Oak with a partially healed blaze and illegible scribing visible, root hole, bears N.42°E., 18.2 ft. 1962  
New - 8" dia., W.Oak double blazed & scribed "¼ S8 CS BT" bears S.51°E., 8.0 ft.  
13" dia., W.Oak double blazed & scribed "¼ S8 CS BT" bears N.62½°E., 27.3 ft.  
11" dia., W.Oak double blazed & scribed "¼ S7 CS BT" bears S.75½°W., 76.0 ft.  
Note - Corner lies at the intersection of a N-S & W running fence lines.  
Compass decl. 16¼°E.