

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6446)

-----  
Set 1/4 sec. post at average dist. from which:  
A B.Oak, 8" dia., bears S.63°E., 73 lks.  
A Laurel, 4" dia., bears N.83°E., 26 lks.

-----  
Alton E. Alspaugh - March 1947 - Subd. Plats Vol. 7 Pg 35A  
-----  
3/4" iron pipe.

-----  
Douglas Co. Surveyors Office - Stephen J. Flause - Terrie Franssen - June 1990 - C.S. File 64/9-15  
-----

Reported as not found.  
Found - A 3/4" I.D. iron pipe protruding 8" above ground as called for in Subdivision Plat B of The Edwin Weaver Estate (Recorded in the Douglas County records as Subdivision Vol. 7 Page 35)  
No evidence of orig. corner monument is found.  
Some trees and stumps were opened in vicinity. No evidence of orig. bearing trees was found. Area has burned over in past, few old trees remain.

-----  
Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 8/24/1999 - C.S. File 66/12-15  
-----

Reported as not found.  
Found - A 3/4" IP per 1947 is found at the intersection of newer fences running north & east, approx. 30 ft. east of this fence corner is an old partially down N-S fence line.  
The 1947 IP was set at proportioned positioned based on the SW corner of sec. 29. An orig. BT was found for the SW corner of sec. 29 approx. 300 ft. North of its 1947 position.  
No orig. BTs found.

-----  
Kristian DeGroot - For: Rick & Gail Weaver - 4/2000 - M132-34  
-----

Set - 5/8"x30" iron rod 26" in the ground with a 2" dia., alum. cap stamped: T29S R5W  
1/4 S 29  
S 32  
2000  
PLS 1941

continued next page

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which new BTs:  
8" Madrona bears N.6°30'13"E., 54.3 ft. bark scribed "¼ S32 BT"  
10" D.Fir bears S.62°34'27"E., 14.4 ft. scribed "¼ S32 BT"  
and new Bearing Objects:  
5/8" x 30" iron rod set 28" in the ground w/plastic cap stamped "BTS ENG-SURV" bears S.6°30'13"W., 20.00 ft  
5/8" x 30" iron rod set 28" in the ground w/plastic cap stamped "BTS ENG-SURV" bears N.62°34'27"W., 20.00 ft