

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Pages 6449-50)  
-----  
Set ¼ sec. post at ave. dist. from which;  
    A Laurel, 24" dia., bears S.35°E., 60 lks.  
    A R. Fir, 6" dia., bears N.45°E., 24 lks.

Douglas Co. Surveyors Office - Frank Cain, Deputy - Jan. 1920  
- "Old" Cor. Book Pg 125 - Vol. 2 Pg 281 - FB 107 PG 14  
-----  
Found - Orig. BT, a Laurel 24" dia., bears S.35°E., 40 lks.  
    I open & find marking plain. Renewed cor. from  
    this BT.  
Set - A post from which;  
    A Pine, 24" mkd: CS ¼ bears N.54°W., 63 lks.  
    A Cedar 13" mkd: CS ¼ bears S.85½°W., 67 lks.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Dale  
McFarland - John Powell - 3/62 - C.S. File 49/64-74  
-----  
Found - Orig. 24" now 36" Laurel, S.35°E., 39.6', previously  
    opened, show good scribing "¼S BT".  
    Both BTs, now stumps, the NW BT shows scribing as  
    recorded by Cain. Cain's cor. bears S.46°E. 12.5'  
    Do not find orig. NE BT.  
I use orig. SE BT to fix position of ¼ cor. I believe that  
Cain either was in error or did not find orig. SE BT. Also,  
my location of ¼ cor. checks location of old fence corner.  
Set - Brass Cap at cor. mkd: ¼ S 8 County Surveyor's  
    T29S R5W S17 Office, 1962  
New BT - 8" R. Fir, bears N.46½°E., 9.2' scribed ¼ S8 CS BT,  
    scribed high.  
Note - Cor. is on steep North slope 40' North of E-W ridge.

Raymond Brown - For: Cow Creek Band of the Umpqua Tribe of  
Indians - Sept. 2006/June 2007 - RM 4-14  
-----  
Fd. brass cap. per (rec)