

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6441)

Set a post for 1/4 sec. cor; from which,
A Black Oak, 12" dia., bears S.10°W., 50 lks.
A Black Oak, 6" dia., bears N.18°W., 30 lks.

Doug. County Surveyors Office - H.L. Eppstein, Co. Surveyor
-Chainmen: B.A. Lane & N.E. Richardson - Axeman: J.T. Black -
Sept. 16/30, 1929 - "Old" Corner Book 128 - Vol. 3 Page 293

The two old down BTs showed ax marks but no scribe marks.
J.T. Black said he had seen scribe marks on tree also stake
there. Set post and piled up rock. Marked:
Fir, 12" dia., N.23°W., 10 lks.
Fir, 10: dia., N.69°E., 45 lks.

Doug. County Surveyors Office - Ben B. Irving, Co. Surveyor
-Witness: R. Carey - May 1945 - C. S. File 38/28

Set 6x12x24" Conglomerate Rock. Trees as recorded.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 8/16/1999 - C.S. File 66/12-12

Reported as not found

Found - Rotted remains of a down D.Fir of uncertain
position, scribing found "1/4 S CS BT" 1929 BT.
(Note no section number on scribed blaze.)
Set - 6" long nail at position of fd BT possible roothole.
Note - Area around corner show evidence being bulldozed.

Kristian DeGroot - For: Rick & Gail Weaver - 4/2000 - M132-34

Set - 5/8"x30" iron rod 24" in ground in a 42" dia., mound of
stone, with a 2" dia., alum. cap stamped:

T29S R5W
1/4
S 29|S 28
2000
PLS 1941

from which new BTS:

continued next page

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

21" D.Fir bears S.51°25'E., 110.0 ft scribed "¼ S28 BT"
21" D.Fir bears S.64°45'W., 82.50 ft scribed "¼ S29 BT"
and new bearing objects
5/8"x30" IR, 26" in the ground w/plastic cap mkd. "BTS
ENG-SURV" bears N.51°19'W., 20.00 ft.
5/8"x30" IR, 26" in the ground w/plastic cap mkd. "BTS
ENG-SURV" bears N.64°38'E., 20.00 ft.