

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6441)

Set a post on the side hill for cor. to secs. 20, 21, 28, & 29; from which,

- A B. Oak, 12" dia., bears N.45°W., 8 lks.
- A B. Oak, 6" dia., bears S.70°W., 8 lks.
- A B. Oak, 8" dia., bears S.45°E., 25 lks.
- A laurel, 5" dia., bears N.45°E., 44 lks.

Doug. County Surveyors Office - G.G. Stewart, Deputy - H.M. Oatman - Jack Black - Frank Drake - Jim Dunnivan - Nov. 28, 1921 - C.S. File 6/4 - Vol. 3 Page 104 - "Old" Corner Book Page 126

Corner consisted of pile of rocks and stake. Found one BT standing and one fallen. I renew from these BTs.

Set - 1" Iron Pipe for corner.

- A 12" Fir, S.82½°W., 7.0'.
- A 18" Fir, S.15°W., 15.8'.
- A 12" Fir, S.63°E., 17.0'.
- A 12" Fir, N.35½°E., 34.5'.

Doug. County Surveyors Office - James W. Byron, Deputy - Dale McFarland - John Powell - Feb. 1962 - C.S. File 49/64-62

Found - 1" I.P. at corner & BTs as recorded except, now 14" Fir bears N.87½°W., not S.82½°W.

SW BT now dead. SE BT down. NE BT dead.

Note - Corner is 36.6' East of a fence corner running North and West. (See sketch in C.S. File 49/64)

New BTs -26" R. Fir, bears S.49°W., 30.0' scribed S29 T29S R5W CS BT.

20" B. Oak, bears S.46°E., 46.3' scribed S28 T29S R5W CS BT.

Found 1" I.P. & BTs by Max Hull - Jan. 1994 - 1994-0029

Found OK by B. Shaner, Sept. 1998 - M129-17

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 8/16/1999 - C.S. File 66/12-13

Found - 1¼" I.D. iron pipe protrudes 4" above a mound of stone. 1921

12" now rotted D. Fir stump, bears N.87½°W., 7.0 ft. (agrees with 1962 rec.) 1921 continued next page

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor Secs 20, 21, 28, & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

18" now down & rotted D.Fir bears S.15°W., 15.8 ft.
(agrees with rec.) 1921
1921 SE BT now gone.
12" now 13" dia., 3 ft. high rotted D.Fir with a
fully healed double blaze scribing found. "S21 CS
BT" bears N.35½°E., 34.5 ft. (agrees w/rec.) 1921
26" now 30" dia., D.Fir with a fully healed double
blaze bears S.49°W., 30.0 ft. (Agrees w/rec.)
1962
20" now 22" dia., 10' tall B.Oak snag with a fully
healed double blaze bears S.46°E., 46.3 ft.
(agrees w/rec.) 1962
Set - 2 3/8" dia., brass cap on a 1 3/8" O.D. by 32" long
iron pipe is set at position of found iron pipe,
protrudes 6" above a mound of stone, mkd:
DOUGLAS COUNTY SURVEYORS
T 29 S
S 20 | S 21 R
S 29 | S 28 5
1999 W
OFFICE
Found IP measured 16" long is set along South edge
of BC/IP is set flush with top of mound of stone.
8" dia., Madrone bark scribed "T29S R5W S28 CS BT"
bears S.76½°E., 26.0 ft. to center of root crown.
15" dia., 4 ft. tall D.Fir stump set 6" screw driver
in top center, bears N.53°W., 39.8 ft.
8" dia., Maple single blazed and scribed "T29S R5W
S29 CS BT" bears S.20°W., 39.7 ft. to center of
root crown.

Fd. BC & 1 rotted BT by N. Hibbs 11/2020 2020-0041