

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs 8, 9, 16, & 17

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6443)

Set a post for cor., from which
A R. Fir, 10" dia., bears S.75°W., 200 lks.
A R. Fir, 30" dia., bears N.25°W., 150 lks.
A R. Fir, 24" dia., bears N.45°E., 112 lks.
A R. Fir, 16" dia., bears S.25°E., 400 lks.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Dale McFarland - John Powell - March 1962 - C.S. File 49/64-72

Found - Orig. NE - NW & SW BTs, all now down & rotted.
We find good reverse scribing on Orig. SW BT all BTs are Pines, not R. Firs.
Set - Conical stone 12"x12"x15" high at corner, chiseled 2" + on North face & small + on pointed top.
New BTs- 14" Pine, bears N.11°E., 114.7' scribed S9 T29S R5W CS BT.
11" R. Fir, bears N.0½°W., 111.0' scribed S8 T29S R5W CS BT.
No trees near South of E - W Line.
Corner is 2' South of E - W Fence.

Mark Smalley, L.S. #2354 - For: Roseburg Forest Products Co. - July/Sept 1993 - M 119-2

Found - Stone with chiseled "+" on top & North
25" Pine, N.11°E., 114.7', healed.
14" Fir, N.0½°W., 111.0', healed.
New BTs- 8" Myrtle, S.74°W., 30.3', "S 17 BT".
8" Pine, N.25°W., 57.2', "S 8 BT".
Set steel fence post in mound of stones S.12°E., 13.0'.