

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs 4, 5, 8, & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6444)

-----  
Set a post, from which;  
A Laurel, 20" dia., bears N.86°W., 90 lks.  
A Laurel, 4" dia., bears S.50°E., 40 lks.  
A Laurel, 4" dia., bears S.5°W., 10 lks.  
A Laurel, 18" dia., bears N.75°E., 70 lks.

Douglas Co. Surveyors Office - Frank Cain, Deputy - Jan. 1920  
- FB 107 Pg 15 - Vol. 2 Pg 280 - "Old" Cor. Book Pg 125

-----  
Reestablished from which  
A Fir, 30" dia, bears N.8½°E., 65 lks.  
A Fir, 18" dia., bears N.77¼°W., 37 lks.  
A Fir, 20" dia., bears S.26½°E., 6 lks.  
A Fir, 24" dia., bears S.24°W., 56 lks.

John H. Markham, Jr. - For: Stomar Lumber Co. - 6/1/52 - C.S. 41/53-1

-----  
All 4 renewed BTs logged.  
At cor. point found wood post scribed and drove a 1" x30" I.P., from which:  
A La. 24" dia., bears West 60.0' - this is an orig. BT fd. scribe & remark S8 BT.  
A La. 24" dia., bears N.35°W., 107.0' mkd: S5 BT  
A Fir, 24" dia., bears N.81°E., 80.0' mkd: S4 BT  
A maple 10" dia., bears S.71°E., 113.0' mkd: S9 BT  
Corner lies on North slope 80.0' East of main side ridge.  
The NW corner of sec. 4 can be seen from here & bears N.7½°W., 5514.0' (Var. 20°00')

Douglas Co. Surveyors Office - James W. Byron, Deputy - Dale McFarland - John Powell - March 1962 - C.S. File 49/64-73

-----  
Found - 1" I.P. at cor.  
10", now 12" Maple S.71°E., 113.0; is OK  
Rescribe, now 30" Laurel, N.35°W., 107.0' S5 T29S R5W CS BT.  
No live trees near to NE or SW

William Ruppert - For: Ron Kuehn - Oct. 1980 - M 84-58 - C.S. File 58/143 (n)

-----  
Found - 1" Iron Pipe  
18" Maple, S.79½°E., 110.8'.  
24" Fir, stump, S.20 3/4°E., 5.6' (Cont. Next Page)

