

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6442)</p> <p>-----</p> <p>Set ¼ sec. post at average dist. from which A B. Oak, 20" dia., bears S.20°W., 50 lks. A B. Oak, 18" dia., bears N.59°E., 37 lks.</p>
<p>Doug. County Surveyors Office - G.G. Stewart, Deputy - H.M. Oatman - Jack Black - Frank Drake - Jim Dunnivan - Nov. 28, 1921 - C.S. File 6/4 - Vol. 3 Pg 104 - "Old" Cor. Book Pg 126</p> <p>-----</p> <p>Renewed from one old BT Set - A 1" Iron Pipe for corner. BTs - Black Oak 24" dia., N.41°W., 34½ lks. White Oak 8" dia., S.38°E., 112 lks.</p>
<p>Geo. J. Wenderoth, Feb. 1944 (could find no record source)</p> <p>-----</p> <p>Found - 8" White Oak, S.38°E., 73.92'. Stump of tree, N.41°W., 22.7', badly decayed. 1" Gal. I. Pipe for corner. New BT - 10" White Oak, S.23°49'W., 30.4'.</p>
<p>Doug. County Surveyors Office - James W. Byron, Deputy - Dale McFarland - John Powell - Feb. 1962 - C.S. File 49/64-64</p> <p>-----</p> <p>Found - Both BT's as recorded by Wenderoth SE BT now snag. SW BT OK. We also find 1" I.Pipe about 3' under surface. Set - Brass cap alongside corner I.P. & mkd: County Surveyor's Office, 1962 $\frac{1}{4} \frac{S \ 21}{S \ 28}$ T29S R5W New BT - 6" Laurel bears N.20°W., 53.6' scribed ¼ S21 CS BT.</p>
<p>Doug. County Surveyors Office - John M. Powell & Crew - 4/18/67 - C. S. File 49/64-82</p> <p>-----</p> <p>Found - 6" Laurel, now 7" N.20°W., 53.6', mkd: ¼ S21 CS BT 20" B. Oak, now 14" S.20°W., 33.0', shows good scar. We do not open. (see 1962 renewal) Brass cap at ¼ cor. set by Co. Surv. Office in 1962. New BT - 6" Laurel S.49½°E., 10.4' mkd: ¼ S28 CS BT.</p>
<p>Doug. County Surveyors Office - Randall Smith, Deputy - Terrie Franssen - April 12, 1991 - C.S. File 64/13-22</p> <p>-----</p> <p>Found - A 2½" dia., 1962 DCSO Brass cap on a 1¼" O.D. I.P. protruding 14" above ground. (Cont. Next Page)</p>

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

1991 DCS0 BC/IP (NW cor. DLC #45 bears East 93.7')
8" now 6" dia. tipped over dead Oak, no scribing visible bears S.38°E., 73.9'.
24" dia., B. Oak, now root hole with decayed wood, bears N.41°W., 22.7'.
10" now 17" dia., W. Oak with a fully healed double blaze bears S.23 3/4°W., 30.4' (agrees with Wenderoth 1944 renewal), J. Powell rec. of S.20°W., 33.0' is the rec. of an orig. BT.
18" now 33" shell of burnt out 2' high oak, bears N.63°E., 24.4' (Rec. N.59°E., 24.4') Orig. BT.
6" now 10" dia., madrone with a fully healed double blaze bears N.23°W., 53.6' (rec. N.20°W., 53.6').
6" now 10" dia., madrone with a partially healed double blaze scribing visible "S28 CS BT" bears S.49½°E., 10.4' (agrees with rec.)
New BT - 8" dia., madrone double blazed and scribed "¼ S21 CS BT" bears N.7°E., 8.6'.

Fd. OK by R. Brown, June 1998 - M129-5
Found OK by N. Hibbs, Dec. 2000 - M132-64
Found OK by B. Ruppert, Sept. 2002 - 2002-0054 A & B
Fd. BC by R. Jackson, 3/2008 - M155-49
Fd. BC & ¾" IR by N. Hibbs 11/2020 2020-0041
Fd. as per rec. 9/2024 by J Terrel, M184-25