

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6444)

Set a ¼ sec. post at ave. dist., from which
A B. Oak, 10" dia., bears S.83°W., 163 lks.
A B. Oak, 16" dia., bears N.33°E., 183 lks.

John H. Markham, Jr. - Witnesses: Geo. Vaughn & E. Stonerod
-7/22-26/50 - C.S. File 40/259-2

Determined by one proportionate measurement.
Set - 3/4"x30" iron pipe, 20" in the ground from which;
13" Alder bears, S.86°W., 25.4', mkd: ¼ S9 T29S R5W
2880 BT.
A log house bears N.57°E., 270.5' to the door.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Dale
McFarland - John Powell - 3/1962 - C.S. File 49/64-73

Found - 1¼" I.P. at corner
15" Alder S.86°W., 25.4', snag shows good bark
scribing.
House to NE burned. Rock foundation still in place.
New BTs- 24" Cedar bears N.83°W., 92.0' scribed ¼ S4 CS BT.
12" DbL. Cedar bears S.45½°E., 105.5', scribed ¼ S9
CS BT.

Mark Smalley, L.S. #2354 - For: Roseburg Forest Products Co.
- July/Sept 1993 - M 119-2

Set - 5/8"x48" IR & Aluminum cap marked "LS 2354"
New BTs -
20" Fir, S.50°W., 180.0', "¼ S BT".
14" Alder, N.63°W., 27.1', "¼ S BT". Bark scribe.
18" Cedar, N.12°W., 345.0', "¼ S BT".
28" Cedar, North, 283.0', "¼ S BT".
POSITION OF MARKHAM'S ¼ CORNER BEARS N.18°06'21"W., 27.07'.
No pipe was found, based on Markham's BTs.