

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. 33 & 34 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6424)

Set a post at proper distance for cor. to secs. 3, 4, 33, & 34, from which

- A B. Oak, 10" dia., bears S.70°E., 9 lks.
- A B. Oak, 10" dia., bears N.45°E., 22 lks.
- A B. Oak, 8" dia., bears N.40°W., 30 lks.
- A B. Oak, 10" dia., bears S.55°W., 72 lks.

John H. Markham, Jr.; Engineer - Witnesses: Geo. & Wm Vaughn - April 22, 1951 - C.S. File 40/259-5

Set by 2 O.B.T.'s.

- A dead B.O. 11' dia., bears N.45°E., 15.0' dist. I found scribe on this O.B.T.
- A B.O. 18" dia., bears S.55°W., 6.0' dist. I remark this O.B.T. S 4 BT.

At corner point set 1"x30" iron pipe, from which

- A Fir 16" dia., bears N.11°E., 14.0' dist. mkd S 34 BT.
- A Fir 8" dia., bears N.53°W., 14.0' dist. mkd S 33, 2880, BT.

B.L.M. Resurvey By Lynn M. Roseberry & James E. Jelley under Group #662. Surveyed Oct. 1967/June 1969. (DCSO records, Vol. 38 Pages 15517 & 15518)

The cor. of secs. 33 & 34 only, perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1951, monumented with an iron pipe, 1" dia., firmly set, projecting 10" above ground, from which the remains of the original bearing trees:

- A root hole, bears N.45°E., 22 lks. dist., with pieces of an oak tree alongside, size indeterminate, with scribe mark T visible on piece of blaze.
 - A black oak, 19" dia., bears S.55°W., 9 lks. dist., with scribe marks S4 BT visible on bark. This tree was rescribed by Markham. (Record, 72 lks)
- and the remains of bearing trees mkd. by Markham
- A fir, 17" dia., bears N.11°E., 23 lks. dist., with healed double blaze.
 - A root hole, bears N.53°E., 23 lks. dist., with a down fir alongside, 8", dia., with healed double blaze.

At the corner point:

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

(Cont. Next Page)

TOWNSHIP 29 RANGE 05 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Cor. Secs. 33 & 34 only

Alias	Description

T 29 S R 5 W
S 33 | S 34
T 30 S R 5 W
S 4
1969

from which a new bearing tree
A fir, 13" dia., bears N.71½°W., 51½ lks. dist., mkd T29S
R5W S33 BT.
Reset iron pipe alongside iron post.

Doug. County Surveyors Office - Randall Smith - Stephen
Flause - Sept. 22, 1989 - C.S. File 64/1-7

Found - A 1969 BLM 3¼" brass cap on a 2½" dia. iron pipe
protruding 9" above ground (from 1969 BLM
resurvey).

1" dia. iron pipe not seen.

10" B. Oak now root hole bears N.45°E., 14.5'
(agrees with record). Orig. BT.

10" B. Oak now root hole bears S.55°W., 6.0' (agrees
with rec.) Orig. BT.

16" now 30" dia. 4' high D. Fir stump with a fully
healed single blaze, bears N.11°E., 14.6' (rec.
N.11°E. 14.0') and 15.2'
BLM resurvey.

8" Fir now root hole bears N.53°W. 14.0' (agrees
rec., BLM 1969 rec. N.53°W. 15.2')

13" now 19" dia. 1' high D. Fir stump with a fully
healed lower blaze, bears N.71½°W. 32.1'. (Rec.
N.71½°W., 34.0' distance is a slope measurement)
From 1969 BLM resurvey.

New BTs - 19" dia. 6' high D. Fir stump, a ½" square x 8¼"
long iron boat spike with a 1 1/8" dia. head is
set through a BT tag on top of stump, top of boat
spike is stamped "B02 1989"

Boat spike bears N.77½°W. 6.9'.

20" dia. 3' high D. Fir stump, a ½" square x 8¼"
long iron boat spike with a 1 1/8" head is set
through a BT tag on top of stump, top of boat
spike is stamped "B01 1989". Boat spike bears
N.47°E., 38.9'

Corner lies in a recent burn and clear cut. No live trees
close.